

**PORTAMATRICULAS ADAPTABLE A KAWASAKI ZX6R 07' -08'**  
**LICENSE SUPPORT ADAPTABLE TO KAWASAKI ZX6R 07' -08'**

**REF : 4456N**



**INSTRUCCIONES DE MONTAJE**

- 1- Desmontar el colín y el soporte de matrícula original.  
*Dismount the back cowl and the original license support.*
- 2- Montar al piloto suministrado(6) fijandolo en los agujeros (D). Montar los silenblocs suministrados (3) en los agujeros (A) del soporte portamatriculas (7) Fijar el soporte en la motocicleta con los tornillos M6X20 (1) y las arandela M6 (2). Pasar los cables eléctricos por la funda de temperatura suministrada (4). Fijar la funda con la brida suministrada (5) en las ranuras (B) y guiarla a través del agujero (C) hasta el interior del colín.  
*Mount the supplied stop light(6) and tight it on the holes (D). Place the wellnuts (3) supplied in the holes (A) of the license support (7). Tight it on the motorcycle using the M6x20 fasteners (1) and M6 washers (2). Place the electrical cables inside the temperature sheath (4) supplied. Tight the sheath with the supplied bridle (5) on the slots (B) and guide it through hole (C) until the cowl interior.*
- 3- Conexión eléctrica. El piloto suministrado incorpora la luz de matrícula, por lo cual el conector de la luz de matrícula original no debe usarse. Conectar el piloto con los tres cables que alimentaban el piloto original. Verificar que frenando aumenta la intensidad del piloto. *Electric connection. The stop light supplied incorporates license light; therefore, the original license light connector does not have to be used. Connect the light supplied with the three cables that feed energy to the original stop light. Verify that the light increases intensity while braking.*

**INSTRUCTIONS TO ASSEMBLE**

**Material suministrado para el montaje en la motocicleta:**

**Material supplied to assemble the license support:**

POSICIÓN	DENOMINACIÓN		CANTIDAD
1	Tornillo M6X20 DIN1001 c/blanco	White M6x20 DIN1001 fastener	4
2	Arandela M6 (Ø18 xØ6 x 1,5) c/blanco	White M6 washer (Ø18 xØ6 x 1,5)	4
3	Conjunto silenblock silicona	Wellnut silicone set	4
4	Funda aislante de temperatura	Temperature insulating sheath	40cm
5	Brida de plástico	Plastic bridle	1
6	Piloto posterior	Stop light	1
7	Soporte c\negro	Support c\black	1
8	Catadrioptico	Reflector	1
9	Desplazador catadrioptico	Support for reflector	1

